

CLAIMS

What is claimed is:

- 5 1. A method of testing a J2EE application, wherein the J2EE application comprises modules, the method comprising the steps of:

identifying (204), from an application deployment descriptor, modules comprised within the J2EE application;

10

identifying, from an identified module, at least one QOS element;

identifying, from the identified QOS element, a software resource to be tested;

15

generating Java test code;

identifying, for the software resource to be tested, a user identification and a user password for a user that is a member of a role intended to protect the software resource; and

20

testing the software resource to be tested by use of the Java test code, including passing as parameters to the Java test code at run time the user identification and user password.

- 25 2. The method of claim 1 wherein:

at least one of the identified modules comprises a web module having a web module deployment descriptor;

- at least one of the identified QOS elements comprises a security-constraint element;
- 5 identifying a software resource to be tested further comprises constructing, from a <web-uri> element in the application deployment descriptor and from a <url-pattern> element in the web module deployment descriptor, a URI that identifies a software resource to be tested;
- 10 testing the software resource by use of the Java test code further comprises invoking the URI, wherein the invoking further comprises transmitting an HTTP request, wherein the HTTP request includes the URI, the user identification, and the user password.
- 15 receiving an HTTP response; and
3. The method of claim 3 wherein testing the software resource by use of the Java test code further comprises passing as a parameter to the Java test code at run time the URI.
- 20
4. The method of claim 3 wherein testing the software resource by use of the Java test code further comprises receiving an HTTP response.
- 25
5. The method of claim 3 wherein testing the software resource by use of the Java test code further comprises determining in dependence upon the HTTP response whether the software resource is protected.

6. The method of claim 1 wherein:

at least one of the identified modules comprises an Enterprise JavaBean module (“EJB module”) having a deployment descriptor;

5

at least one of the identified QOS elements comprises a <method-permission> restraint element;

the <method-permission> restraint element comprises:

- 10 a first <method-name> sub-element having a first <method-name> sub-element value, and
 a first <ejb-name> sub-element having a first <ejb-name> sub-element value;

15 the identified software resource to be tested comprises a JavaBean method;

identifying a software resource to be tested comprises the further steps of:

- 20 finding in a deployment descriptor for the identified EJB module one or more <enterprise-bean> elements having nested <ejb-name> sub-elements having values equal to the first <ejb-name> sub-element value, wherein each found <enterprise-bean> element comprises:

- 25 the nested <ejb-name> sub-element,
 a <home> nested sub-element,
 a <remote> nested sub-element, and
 an <ejb-class> nested sub-element; and

identifying, for each found <enterprise-bean> element, a method signature having a method name equal to the first <method-name> sub-element value; and

- 5 testing the software resource by use of the Java test code comprises the further steps of:

looking up the JavaBean home by use of a JNDI home name for the software resource;

- 10 creating, by use of the JavaBean home, an instance of the JavaBean; and
- invoking, in the created instance, the protected JavaBean method.

- 15 8. The method of claim 6 wherein testing the software resource by use of the Java test code further comprises passing as a parameter to the Java test code at run time the JNDI name for the JavaBean method;
- 20 9. The method of claim 6 wherein testing the software resource by use of the Java test code further comprises logging in to an application environment by use of the user identification and the user password.
- 25 10. The method of claim 6 wherein testing the software resource by use of the Java test code further comprises reporting whether invoking the protected JavaBean method succeeded.

11. The method of claim 6 wherein identifying, for each found <enterprise-bean> element, a method signature having a method name equal to the first <method-name> sub-element value further comprises identifying, for each found <enterprise-bean> element, by use of Java reflection and the value of the <ejb-class> element, a method signature having a method name equal to the first <method-name> sub-element value.

12. A system of testing a J2EE application, wherein the J2EE application comprises modules, the system comprising:

5 means for identifying (204), from an application deployment descriptor, modules comprised within the J2EE application;

means for identifying, from an identified module, at least one QOS element;

10 means for identifying, from the identified QOS element, a software resource to be tested;

means for generating Java test code;

15 means for identifying, for the software resource to be tested, a user identification and a user password for a user that is a member of a role intended to protect the software resource; and

20 means for testing the software resource to be tested by use of the Java test code, including means for passing as parameters to the Java test code at run time the user identification and user password.

13. The system of claim 12 wherein:

25 at least one of the identified modules comprises a web module having a web module deployment descriptor;

at least one of the identified QOS elements comprises a security-constraint element;

means for identifying a software resource to be tested further comprises means for
5 constructing, from a <web-uri> element in the application deployment descriptor and from a <url-pattern> element in the web module deployment descriptor, a URI that identifies a software resource to be tested;

means for testing the software resource by use of the Java test code comprises:

10

means for invoking the URI wherein the means for invoking further comprises means for transmitting an HTTP request, wherein the HTTP request includes the URI, the user identification, and the user password.

15

14. The system of claim 13 wherein means for testing the software resource by use of the Java test code further comprises means for passing as a parameter to the Java test code at run time the URI.

15. The system of claim 13 wherein means for testing the software resource by use of

20

the Java test code further comprises means for receiving an HTTP response.

16. The system of claim 13 wherein means for testing the software resource by use of the Java test code further comprises means for determining in dependence upon the HTTP response whether the software resource is protected.

25

17. The system of claim 12 wherein:

at least one of the identified modules comprises an Enterprise JavaBean module (“EJB module”) having a deployment descriptor;

5

at least one of the identified QOS elements comprises a <method-permission> restraint element;

the <method-permission> restraint element comprises:

10

a first <method-name> sub-element having a first <method-name> sub-element value, and

a first <ejb-name> sub-element having a first <ejb-name> sub-element value;

15

the identified software resource to be tested comprises a JavaBean method;

means for identifying a software resource to be tested comprises:

20

means for finding in a deployment descriptor for the identified EJB module one or more <enterprise-bean> elements having nested <ejb-name> sub-elements having values equal to the first <ejb-name> sub-element value, wherein each found <enterprise-bean> element comprises:

25

the nested <ejb-name> sub-element,
a <home> nested sub-element,
a <remote> nested sub-element, and

an <ejb-class> nested sub-element; and

means for identifying, for each found <enterprise-bean> element, a
method signature having a method name equal to the first <method-
name> sub-element value; and
5

means for testing the software resource by use of the Java test code comprises:

means for looking up the JavaBean home by use of a JNDI home name
10 for the software resource;

means for creating, by use of the JavaBean home, an instance of the
JavaBean;

15 means for invoking, in the created instance, the protected JavaBean
method.

19. The system of claim 17 wherein means for testing the software resource by use of
the Java test code further comprises means for passing as a parameter to the Java
20 test code at run time the JNDI name for the JavaBean method;

20. The system of claim 17 wherein means for testing the software resource by use of
the Java test code further comprises means for logging in to an application
environment by use of the user identification and the user password.

25
21. The system of claim 17 wherein means for testing the software resource by use of
the Java test code further comprises means for reporting whether invoking the
protected JavaBean method succeeded.

22.

- The system of claim 17 wherein means for identifying, for each found <enterprise-bean> element, a method signature having a method name equal to the first <method-name> sub-element value further comprises means for identifying, for each found <enterprise-bean> element, by use of Java reflection and the value of the <ejb-class> element, a method signature having a method name equal to the first <method-name> sub-element value.

23.

A computer program product of testing a J2EE application, wherein the J2EE application comprises modules, the computer program product comprising:

5

a recording medium;

means, recorded on the recording medium, for identifying (204), from an application deployment descriptor, modules comprised within the J2EE application;

10

means, recorded on the recording medium, for identifying, from an identified module, at least one QOS element;

15

means, recorded on the recording medium, for identifying, from the identified QOS element, a software resource to be tested;

means, recorded on the recording medium, for generating Java test code;

20

means, recorded on the recording medium, for identifying, for the software resource to be tested, a user identification and a user password for a user that is a member of a role intended to protect the software resource; and

25

means, recorded on the recording medium, for testing the software resource to be tested by use of the Java test code, including means for passing as parameters to the Java test code at run time the user identification and user password.

24. The computer program product of claim 23 wherein:

at least one of the identified modules comprises a web module having a web module deployment descriptor;

5

at least one of the identified QOS elements comprises a security-constraint element;

means, recorded on the recording medium, for identifying a software resource to
10 be tested further comprises means for constructing, from a <web-uri> element in
the application deployment descriptor and from a <url-pattern> element in the
web module deployment descriptor, a URI that identifies a software resource to be
tested;

15 means, recorded on the recording medium, for testing the software resource by use
of the Java test code comprises:

means, recorded on the recording medium, for invoking the URI wherein the
means for invoking further comprises means for transmitting an HTTP request,
20 wherein the HTTP request includes the URI, the user identification, and the user
password.

25. The computer program product of claim 24 wherein means for testing the
software resource by use of the Java test code further comprises means for passing
the URI as a parameter to the Java test code at run time.

26. The computer program product of claim 24 wherein means for testing the software resource by use of the Java test code further comprises means for receiving an HTTP response.
- 5 27. The computer program product of claim 24 wherein means for testing the software resource by use of the Java test code further comprises means for determining in dependence upon the HTTP response whether the software resource is protected.
- 10 28. The computer program product of claim 23 wherein:
- at least one of the identified modules comprises an Enterprise JavaBean module (“EJB module”) having a deployment descriptor;
- 15 at least one of the identified QOS elements comprises a <method-permission> restraint element;
- the <method-permission> restraint element comprises:
- 20 a first <method-name> sub-element having a first <method-name> sub-element value, and
 a first <ejb-name> sub-element having a first <ejb-name> sub-element value;
- 25 the identified software resource to be tested comprises a JavaBean method;
 means, recorded on the recording medium, for identifying a software resource to be tested comprises:

means, recorded on the recording medium, for finding in a deployment descriptor for the identified EJB module one or more <enterprise-bean> elements having nested <ejb-name> sub-elements having values equal to the first <ejb-name> sub-element value, wherein each found <enterprise-bean> element comprises:

5

the nested <ejb-name> sub-element,

10

a <home> nested sub-element,

a <remote> nested sub-element, and

an <ejb-class> nested sub-element; and

15

means, recorded on the recording medium, for identifying, for each found <enterprise-bean> element, a method signature having a method name equal to the first <method-name> sub-element value; and

20

means, recorded on the recording medium, for testing the software resource by use of the Java test code comprises:

means, recorded on the recording medium, for looking up the JavaBean home by use of a JNDI home name for the software resource;

25

means, recorded on the recording medium, for creating, by use of the JavaBean home, an instance of the JavaBean;

means, recorded on the recording medium, for invoking, in the created instance, the protected JavaBean method.

29. The computer program product of claim 28 wherein means for testing the software resource by use of the Java test code further comprises means, recorded on the recording medium, for passing as a parameter to the Java test code at run time the JNDI name for the JavaBean method;
- 5
30. The computer program product of claim 28 wherein means for testing the software resource by use of the Java test code further comprises means, recorded on the recording medium, for logging in to an application environment by use of the user identification and the user password.
- 10
31. The computer program product of claim 28 wherein means for testing the software resource by use of the Java test code further comprises means, recorded on the recording medium, for reporting whether invoking the protected JavaBean method succeeded.
- 15
32. The computer program product of claim 28 wherein means for identifying, for each found <enterprise-bean> element, a method signature having a method name equal to the first <method-name> sub-element value further comprises means for identifying, recorded on the recording medium, for each found <enterprise-bean> element, by use of Java reflection and the value of the <ejb-class> element, a method signature having a method name equal to the first <method-name> sub-element value.
- 20